

NX-3220/3320

VHF/UHF MULTI-PROTOCOL DIGITAL & ANALOG PORTABLE RADIOS

This versatile handheld radio supports both NXDN® and DMR digital protocols as well as mixed digital & FM analog operation, enabling it to serve with distinction in a wide range of enterprise and operation critical applications. Compact yet designed with durability in mind, it's packed with convenient features like Bluetooth® for hands-free operation and built-in GPS. Three different models are available: Full Keypad model with LCD, Standard Keypad model with LCD and a large 4-way D-pad, and the Basic Model without LCD or keypad. Additionally, for expansion capability a software license certification system facilitates extensive customization.



Full Keypad Model
Standard & Basic Models



7-color Light Bar Indicator

FEATURES

- Multi-protocol digital radio: Designed to operate NXDN® or DMR digital, and FM analog protocols
- NXDN® Conventional and Type-C & Gen2 Trunking
- DMR Tier II & Site Roaming
- Mixed Digital & FM Analog Operation allows gradual migration at your own pace
- 4-Line Basic Frame (2-Line Main/Sub-LCD, icon & key guide) / 14 Characters
- 5-Line Text Message Frame (3 Lines of Text, icon & key guide)
- 7-color Light Bar Indicator on the top panel. Individual color can be set for each channel.
- 4-way Directional-pad (D-pad) for intuitive control and operation
- Built-In GPS Receiver/Antenna for effective fleet management
- Built-in Bluetooth® for hands-free operation - Applicable Bluetooth profiles: HSP (Headset Profile provided) and SPP (Serial Port Profile available as an option)
- Renowned KENWOOD Audio Quality achieved with Active Noise Reduction (ANR) that utilizes built-in DSP
- Software DES and AES Encryptions for NXDN Conventional Trunking and AES for DMR Conventional protocols
- Built-in Motion Sensor (Man-down, Stationary and Motion Detection)
- IP54/55/67 and MIL-STD-810 C/D/E/F/G
- 1 Watt Audio Output Power
- UHF: 120 MHz capability
- Available models: Full Keypad (w/ LCD and full keypad), Standard Keypad (w/ LCD and 4-way large D-pad/4 key), and Basic (w/o LCD and keypad)
- 260 CH/128 Zones (64 CH/4 Zones for Basic model)
- Maximum of 1,000 CH/Radio with option

- Paging Call
- Emergency Call
- Status/Text Message
- Remote Stun/Kill/Check

DIGITAL – NXDN® MODE

- NXDN Type-C & Gen2 Trunked
- NXDN Conventional
- 6.25 & 12.5 kHz Channels
- All Group Call
- Over-the-Air Alias (OAA)
- Over-the-Air Programming (OTAP)

DIGITAL – DMR MODE

- Complies with ETSI DMR Tier II standards
- Two-slot TDMA in 12.5 kHz channels
- Call Interruption
- Dual-slot Direct Mode
- ARC4 Encryption
- Energy Efficient

ANALOG - FM MODE

- Conventional & LTR Trunking
- FleetSync/II: PTT ID ANI / Caller ID Display, Selective Group Call, Emergency Status / Text Messages
- MDC-1200: PTT ID ANI / Caller ID Display, Emergency, Radio Check / Inhibit
- QT / DQT, 2-Tone
- Built-in Voice Inversion Scrambler



Multi-Protocol

Unsurpassed interoperability for Public Safety and Enterprise radio users with the freedom to migrate at your own pace.



Gen2

Scalable server-based system architecture for management of NEXEDGE wide area digital communications systems.



Klarity

The ultimate level of sound clarity technology combining Optimization, advanced Sound Analysis and Active Noise Reduction.

Accessories

NX-3220/3320 Portable Radios

<ul style="list-style-type: none"> ■ KNB-55L/57L/78L Li-ion Battery Pack (7.4V/1480mAh, 7.4V/2000mAh, 7.4V/2860mAh) 	<ul style="list-style-type: none"> ■ KMB-30 Mounting Bracket (for KSC-256) 	<ul style="list-style-type: none"> ■ KRA-26 VHF Helical Antenna 	<ul style="list-style-type: none"> ■ KHS-7A Lightweight Single Muff Headset 	<ul style="list-style-type: none"> ■ KHS-27A Head Set (with D-Ring In-Line PTT)
<ul style="list-style-type: none"> ■ KNB-56N Ni-MH Battery Pack (7.2 V/1400 mAh) 	<ul style="list-style-type: none"> ■ KVC-4 Rapid Rate Vehicular Charger Adapter (for KSC-25LSK/SK) 	<ul style="list-style-type: none"> ■ KRA-27 UHF Whip Antenna 	<ul style="list-style-type: none"> ■ KHS-8BL 2-wire Palm Mic with Earphone (Black) 	<ul style="list-style-type: none"> ■ KBH-11 Belt Clip (2.5")
<ul style="list-style-type: none"> ■ KBP-5 Battery Case (6 AA) 	<ul style="list-style-type: none"> ■ KRA-22 VHF Low Profile Helical Antenna 	<ul style="list-style-type: none"> ■ KRA-28 Broadband VHF Whip Antenna 	<ul style="list-style-type: none"> ■ KHS-10 Headset (Single Muff Single Muff & In-line PTT Heavy Duty Behind-the-Head) 	<ul style="list-style-type: none"> ■ KPG-180P OTAP Manager
<ul style="list-style-type: none"> ■ KSC-25LSK/25SK Rapid Charger (Li-ion Only/Tri-Chem) 	<ul style="list-style-type: none"> ■ KRA-23 UHF Low Profile Helical Antenna 	<ul style="list-style-type: none"> ■ KEP-2 Earphone Kit for KMC-45D (2.5mm plug) 	<ul style="list-style-type: none"> ■ KHS-22 Head Set 	<ul style="list-style-type: none"> ■ KLH-208P Heavy Duty Leather Case for use with KNB-57L/55L/56N/KPB-5 Batteries
<ul style="list-style-type: none"> ■ KSC-256K Multiple Charger (6-pocket) 	<ul style="list-style-type: none"> ■ KRA-25 High Gain Whip Antenna 	<ul style="list-style-type: none"> ■ KMC-45D Speaker Microphone (IP54/55 & TDMA) 	<ul style="list-style-type: none"> ■ KHS-26 Head Set (with Ear Bud In-Line PTT) 	<ul style="list-style-type: none"> ■ KLH-212P Heavy Duty Leather Case for use with KNB-78L Battery

All accessories may not be available in all markets.
Contact an authorized Kenwood dealer for details and complete list of all accessories.

Specifications

	NX-3220	NX-3320		NX-3220	NX-3320
GENERAL					
Frequency Range	136-174 MHz		400-520 MHz		
Max. Channels Per Radio	Up to 1000 CH with option				
Number of Channels	260 (64 for no LCD models)				
Number of Zones	128 (4 for no LCD models)				
Channel Spacing	12.5/15/25/30 kHz		12.5/25 kHz		
Analog	6.25 kHz/12.5 kHz				
Digital					
Power Supply	7.5V DC ± 20%				
Battery Life 5-5-90	(FDMA/TDMA)				
KNB-55L (1,480 mAh)	Approx. 8 hours / Approx. 9.5 hours				
KNB-56N (1,400 mAh)	Approx. 8 hours / Approx. 9 hours				
KNB-57L (2,000 mAh)	Approx. 11 hours / Approx. 13.5 hours				
Operating Temperature	-22°F to +140°F (-30°C to +60°C)				
Frequency Stability	±2.0 ppm		±1.0 ppm		
Dimensions	(W x H x D) Projections Not Included				
Radio Full Keypad Model	2.20 x 4.71 x 1.43 in (56 x 119.6 x 36.4 mm)				
KNB-55L (1,480 mAh)	2.20 x 4.71 x 1.43 in (56 x 119.6 x 36.4 mm)				
KNB-56N (1,400 mAh)	2.20 x 4.71 x 1.68 in (56 x 119.6 x 42.7 mm)				
KNB-57L (2,000 mAh)	2.20 x 4.71 x 1.53 in (56 x 119.6 x 39 mm)				
Weight Radio Full Keypad Model	7.8 oz (220 g)				
KNB-55L (1,480 mAh)	11.1 oz (315 g)				
KNB-56N (1,400 mAh)	14.5 oz (410 g)				
KNB-57L (2,000 mAh)	12.0 oz (340 g)				
IC Certification	282F-479000		282F-479100		
RECEIVER					
Sensitivity	NXDN® 6.25 kHz Digital (3% BER)		0.20 µV		
	NXDN® 12.5 kHz Digital (3% BER)		0.25 µV		
	DMR 12.5 KHz Digital (5% BER)		0.30 µV		
	DMR 12.5 KHz Digital (1% BER)		0.45 µV		
	Analog (12dB SINAD)		0.25 µV		
Selectivity	Analog @ 12.5 kHz		65 dB		
	Analog @ 25 kHz		72 dB		
Intermodulation	70 dB				
Spurious Rejection	70 dB				
Audio Distortion	3%				
Audio Output Power	500 mW/8Ω (3% Distortion) / 1,000 mW/8Ω (5% Distortion)				
TRANSMITTER					
RF Power Output (High / Mid / Low)	5 W / 4 W / 1 W				
Spurious Emission	70 dB				
FM Hum & Noise					
Analog @ 12.5 kHz	40 dB				
Analog @ 25kHz	45 dB				
Audio Distortion	3%				
Digital Protocol	ETSI TS 102 361-1, -2, -3				
Emission Designator	16K0F3E, 11K0F3E, 8K30F1E, 8K30F1D, 8K30F7W, 7K60FXD, 7K60FXE, 4K00F1E, 4K00F1D, 4K00F7W, 4K00F2D				

Analog measurements made per TIA603. Specifications are measured according to applicable standards. Specifications shown are typical and subject to change without notice, due to advancements in technology.

The Bluetooth word mark and logos are registered trademarks owned by the Bluetooth SIG, Inc. NXDN® is a registered trademark of JVCKENWOOD Corporation and Icom Inc. NEXEDGE® & FleetSync® are a registered trademarks of JVCKENWOOD Corporation. All other trademarks are the property of their respective holders.

MIL-STD & IP

MIL Standard	MIL 810C Methods/Procedures	MIL 810D Methods/Procedures	MIL 810E Methods/Procedures	MIL 810F Methods/Procedures	MIL 810G Methods/Procedures
Low Pressure	500.1/Procedure I	500.2/Procedure I, II	500.3/Procedure I, II	500.4/Procedure I, II	500.5/Procedure I, II
High Temperature	501.1/Procedure I, II	501.2/Procedure I, II	501.3/Procedure I, II	501.4/Procedure I, II	501.5/Procedure I, II
Low Temperature	502.1/Procedure I	502.2/Procedure I, II	502.3/Procedure I, II	502.4/Procedure I, II	502.5/Procedure I, II
Temperature Shock	503.1/Procedure I	503.2/Procedure I	503.3/Procedure I	503.4/Procedure I, II	503.5/Procedure I
Solar Radiation	505.1/Procedure I	505.2/Procedure I	505.3/Procedure I	505.4/Procedure I	505.5/Procedure I
Rain	506.1/Procedure I, II	506.2/Procedure I, II	506.3/Procedure I, II	506.4/Procedure I, III	506.5/Procedure I, III
Humidity	507.1/Procedure I, II	507.2/Procedure II, III	507.3/Procedure II, III	507.4	507.5/Procedure II
Salt Fog	509.1/Procedure I	509.2/Procedure I	509.3/Procedure I	509.4	509.5
Dust	510.1/Procedure I	510.2/Procedure I	510.3/Procedure I	510.4/Procedure I, III	510.5/Procedure I
Vibration	514.2/Procedure VIII, X	514.3/Procedure I	514.4/Procedure I	514.5/Procedure I	514.6/Procedure I
Shock	516.2/Procedure I, II, V	516.3/Procedure I, IV	516.4/Procedure I, IV	516.5/Procedure I, IV	516.6/Procedure I, IV
International Protection Standard					
Dust & Water Protection*	IP54/55/67				

*Radio must equip 2PIN accessory cover.

KENWOOD

JVCKENWOOD Canada Inc.
Canadian Headquarters and Distribution
6070 Kestrel Road, Mississauga, Ontario, Canada L5T 1S8
www.kenwood.com/ca



ISO9001 Registered
JVCKENWOOD Corporation
ADS#39917 Printed in USA